

# Product Data Sheet

## Inspection Chamber KS 30-PE

Order No. 4033



### Technical Data

#### Inspection Chamber KS 30

Order No. 4033

Made of 100% polyethylene, UV resistant, with solid, lockable cover and load distributing plates.

Height:	ca. 300 mm
Dimensions:	ca. 300 x 300 mm
Weight:	ca. 6.0 kg
Colour:	black

Inspection chamber to secure the inspection of roof outlets or other components within intensive green roof build-ups.



#### Accessories for KS 30:

##### Extension piece

Order No. 4016

Made of 100% polyethylene, for the extension of the Inspection Chamber KS 30-PE and Irrigation Unit B 32 in segments.


Height:	ca. 150 mm
Weight:	ca. 2.0 kg

### Features

- suitable for green roof system build-ups up to 300 mm in height
- extension pieces for vertical adjustment in segments
- 100% polyethylene
- with load-distributing support plates
- footstep stability Class K according to German Standard DIN 19599
- solid, detachable cover, lockable
- with PE sheet collar for consistent filter sheet connection

### Application Example

#### System "Roof Garden"



Plant layer  
System Substrate "Roof Garden"  
Filter Sheet SF  
Floradrain® FD 60, infilled with Zincolit® Plus  
Protection Mat ISM 50  
Roof construction with root resistant waterproofing

### Specification Suggestion

Inspection chamber made of 100% polyethylene; with detachable cover and load distributing support plates, dimensions ca. 300 x 300 mm, height ca. 300 mm, weight ca. 6 kg, colour black, delivery and installation

according to manufacturer's instructions.

Make: ZinCo Inspection Chamber KS 30-PE  
Enquiries: ZinCo GmbH,  
Phone: +49 7022 6003-0